

MÜÜRISEGU M 200

MASONRY MORTAR M200

High quality masonry mortar with polymeric additives for internal and external use.

12 different colours available

COMPOSITION

- Quartz sand (max. grain \varnothing 0.8 mm), white or grey Portland cement, lime, polymers, plasticizers, mineral colouring (in coloured mortar)

APPLICATIONS

- For constructing of masonry, facades, chimneys and fireplaces from bricks, sand lime bricks and various blocks.

PREPARATION OF USE

- Pour necessary amount of powder into suitable container or mixer.
- Add water in amount 13-14% of powder weight. (3,25 – 3,5 litres for 25 kg bag)
- Stir mechanically or manually until compound is homogenous.
- Leave compound for a while and stir again.
- Use prepared plaster during 4 hours.

MORTAR CONSUMPTION

To one brick with dimensions	250x120x65 mm	0,6-0,8 kg of mortar
To one perforated brick with dimensions	250x120x65 mm	0,8-1,0 kg of mortar
To one facade concrete block with dimensions	190x 90x57 mm	0,4-0,5 kg of mortar
To one exclay block with dimensions	490x200x185 mm	1,2-1,4 kg of mortar

STORAGE

- Packed powder should be stored in dry room
- Storage time 1 year