

NAKS-3

FAST-SETTING TILE ADHESIVE

Used indoors and outdoors.

USAGE

- Tile adhesive based on fast-setting grey cements designed for fast application.
- Suitable to be used on all mineral substrates, such as plaster, concrete, stone, gypsum boards, etc. Also to be used on substrates already covered, stoves, hot walls, etc.
- Used for installing wall and floor tiles in dry, humid and wet conditions.
- Suitable for installing glazed, clinker and stone tiles.
- For installing gypsum boards on mineral surfaces.

MIXING

- Pour mixture into a mixer or a bowl with a wide opening.
- Add water 25% of the weight of the mixture (6,25 l per 25 kg package or 1,25 l per 5 kg box)..
- Mix carefully with a mixer.
- Wait for 3-5 minutes and mix moderately once again.
- Ready mixture to be used within 1 hour after adding water. Adding water at a later stage does not recover the initial properties of the mixture.

APPLICATION

- Moisture-sensitive surfaces to be primed with Uninaks MOISTURE-PROOF MIXTURE. Weak substrates to be strengthened with Uninaks ADHESIVE DISPERSION.
- Apply mixture with the aid of a spatula onto a floor or wall surface. Mixture can also be applied directly onto every individual tile.
- Apply mixture on an area you are able to cover with tiles within 5 minutes.
- Tiles already installed can be adjusted within 3-5 minutes.

CURING

- The installed tiles are ready for jointing works in 2 hours.
- The installed tiles can be walked on and are ready for jointing works in 3-4 hours.
- The floor must not be loaded before 24 hours.

LIMITATIONS – WARNINGS

- The room, mixture and surface temperature must be above +10 °C during the tiling process and 24 hours after that. Lower temperatures prolong the curing process and interfere with the quality of the mixture.
- Sub-floor heating **MUST NOT** be used while tiling and for 24 hours before and after tiling.
- This product contains cement. Contact with water causes an alkaline reaction. Can cause skin irritation. Upon contact with eyes rinse immediately with plenty of water. For more specific information please refer to the Safety Data Sheet.
- Avoid contact of residual mixture with a sewerage system.

CONSUMPTION

- Consumption of the mixture for installing 1 m² of tiles is 3-4 kg, depending on the substrate and thickness of the layer.

STORAGE

- Dry and in original condition 1 year.