

MATERIAL SAFETY DATA SHEET

In accordance with the EC REACH Regulation No. 1907/2006 and No. 453/2010 Classified and labelled in accordance with EC regulation No. 1272/2008 (CLP).

SECTION 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

1.1 Product identifier Trade name

Põrandanaks NAKS PN30

UniTherm 1 Naks+P UniTherm 2 Nobenaks NAKS Plaster mix NAKS KS Granite concrete M500 Fibre plaster Siler-3

> Light-coloured plaster mix NAKS HKS Quick-set jointing concrete

NAKS KVB

Lightweight concrete LC18 Vertical jointing concrete NAKS VVB50

Self-stressing concrete NAKS M400

CUBE

Sängitusbetoon C35

Product type: cement based construction

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use: construction

1.3. Details of the supplier of the safety data sheet

Manufacturer:

Uninaks AS 1 Valuste Street 90303 Lihula Telephone: +372 656 5744

Fax: +372 656 5744 uninaks@uninaks.ee

01.02.2024 Version: 1.1

1.4. Emergency telephone number

Telephone number. name and address:

E-mail:

Poisoning Information Centre (http://www.16662.ee) Tel: 16662. Available for calling 24 hours a day from 09:00 AM on Monday till 09:00 AM on Saturday for general public and

health care professionals.

The centre is closed on weekends. For calls from abroad:

+372 79 43 794

SECTION 2. HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

See Section 16 for full text of the R-phrases

DPD: Xi: R37/38-41

CLP: Skin Irrit. 2: H315 - Eve dam. 1: H318 - STOT SE 3: H335

The effect may cause redness and stinging of the eyes and lacrimation, itching in the nose and throat, and coughing. Dust from the product may irritate eyes, skin and respiratory tract. May cause permanent damage to the eyes. Dangerous when moist: the product causes burns to the eyes, skin and mucous membranes. Prolonged inhalation of the dust particles may bring about the danger of pulmonary infection.

2.2. Label elements

Hazard pictograms:



Signal word: Caution

Hazard statements

H315 Causes skin irritation. H318 Causes serious eye damage. H335 May cause respiratory irritation. statements

P102 Keep out of reach of children.

P261 Avoid breathing dust.

P280 Wear protective gloves/protective clothing/eye protection/face

P301/310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Rem

contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT/vPvB Not relevant

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains cement and quartz sand (inhalable quartz < 0.1%). The product contains chromium(VI) that remains below the permitted limit of 2 mg/kg in unopened packages within 12 months.

Hazardous ingredients

CAS	EINECS	Chemical name	Concentration	Classification
65997-15-1	266-043-4	Portland cement	30-60%	DSD: Xi, R37/38-41 CLP: STOT SE 3; H335 Skin irrit. 2; H315 Eye dam. 1; H318
14808-60-7	238-878-4	Quartz	10-60%	•

SECTION 4. FIRST AID MEASURES

4.1. Description of first aid measures

Keep immobile. Seek fresh air. Administer oxygen or give artificial

respiration, if needed. If symptoms persist, seek medical attention. Show

these safety precautions to the doctor.

If exposed, wash eyes or skin immediately using a copious amount of water for 15 minutes, and remove contaminated clothes and footwear. Seek Skin contact:

medical attention if the irritation grows or persists. Show these safety

precautions to the doctor.

Eye contact: Rinse promptly with plenty of water, including under the eyelids, for at least

15 minutes. Remain under medical surveillance. Show these safety

Ingestion: Do not induce vomiting. Drink water. Call a doctor immediately.

4.2. Most important symptoms and effects, both acute and delayed

Causes serious eye damage. Causes skin irritation. May cause respiratory irritation.

4.3 Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER/doctor.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Show these safety precautions to the doctor.

SECTION 5. FIREFIGHTING MEASURES

5.1. Extinguishing media

Use a water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2. Specific hazards arising from the substance or mixture

The product is not flammable. Cooling water that has come into contact with the product could be corrosive.

5.3. Advice for firefighters

Use self-contained breathing apparatus and safety shoes

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures



MATERIAL SAFETY DATA SHEET

In accordance with the EC REACH Regulation No. 1907/2006 and No. 453/2010 Classified and labelled in accordance with EC regulation No. 1272/2008 (CLP).

Wear personal protective equipment. Avoid contact of the substance with the skin, eyes, and clothing. Provide adequate ventilation. See Section 8.

6.2. Environmental precautions

Do not empty into drains connected to surface water or sanitary sewers. Immediately inform competent authorities if the product has reached natural bodies of water.

6.3. Methods and material for containment and cleaning up

Sweep up and place in a proper container for disposal. Use an appropriate vacuum cleaner. Dispose of according to applicable legislation.

6.4. Reference to other sections

Data not available.

SECTION 7. HANDLING AND STORING

7.1. Precautions for safe handling
Wear personal protective equipment. Handle in accordance with good occupational hygiene and safety practice. Wash face and hands before breaks and immediately after handling the product. Provide adequate ventilation. Avoid contact of the substance with the skin, eyes, and clothing. Do not inhale dust.

7.2. Conditions for safe storage, including any incompatibilities

Store well-closed in a dry, cool and well-ventilated place. Use open packages as quickly as possible.

7.3. Specific end use(s):

Data not available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

Chemical name Quartz, inhalable Total quartz Mineral dust, inert, inhalable Mineral dust, inert Exposure limit 0,1 mg/m³ 0,3 mg/m³ 14808-60-7

8.2. Control parameters

Appropriate engineering controls

Handle in accordance with good occupational hygiene and safety practice. Provide adequate ventilation. Avoid exceeding exposure limits (see Section 8).

Personal protection

measures

Respiratory protection

Use suitable respiratory protective device in the case of insufficient ventilation. Respirators that are permeable to dust are depreciated. Respirator equipped with a particle

filter (EN 143) (P2)

Hand protection Protective gloves, rubber gloves (EN 374), nitrile rubber.

Eye/face protection Safety goggles with face protection in accordance with

Personal protection equipment to be used: appropriate Skin protection

protective gloves, safety goggles and protective clothing

(EN 340).

Environmental exposure

Data not available.

controls

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance:

Relative density:

Water-soluble Solubility:

9.2. Other information Data not available.

SECTION 10. STABILITY AND REACTIVITY

10.1. Reactivity

Stable under normal conditions.

10.2. Chemical stability

Stable under normal conditions. Keep in a dry place.

10.3. Possibility of hazardous reactions

Data not available

10.4. Conditions to avoid

Keep packaged product away from moisture

10.5. Incompatible materials

Reacts violently with acids. Wet mortar may react with aluminium powder and alkalineearth metals, producing hydrogen.

10.6. Hazardous decomposition products

Stable under normal conditions

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Dust from the product may irritate the respiratory tract and cause

itching in the throat, respiratory involvement, chest pain and

cough

Dust from the product may irritate the skin. May cause burns on Skin contact:

the skin and mucous membranes

Eye contact: Dust from the product may cause redness and stinging of the

eyes and lacrimation. May cause permanent damage to the

Ingestion: Ingestion may cause serious irritation in the mouth, oesophagus

and gastrointestinal tract.

Long-term effects: Prolonged inhalation of the dust particles may bring about the

danger of pulmonary infection

SECTION 12. ECOLOGICAL INFORMATION

The product is not considered to be dangerous to the environment.

12.2. Persistence and degradability

Methods for the determination of the biodegradability cannot be applied to inorganic substances

Data regarding chemical degradation are not available.

12.3. Bioaccumulative potential

Avoid release of the product into the environment

12.4. Mobility in soil

Do not empty residue into drains.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

Data not available.

SECTION 13. WASTE DISPOSAL

13.1. Waste treatment methods

Dispose of waste in an appropriate waste disposal facility

Waste code: 170903

170904

Other construction and demolition waste (including mixed

waste) containing hazardous substances Mixed construction and demolition wastes other than those

mentioned in 17 09 01, 17 09 02 and 17 09 03

SECTION 14. TRANSPORT INFORMATION

14.1. UN number

Not classified as hazardous substance in accordance with regulatory rules regarding transportation.

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packaging group

14.5. Environmental hazards -

14.6. Special precautions for user

Not regulated

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not regulated

SECTION 15. REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Data not available

15.2. Chemical safety assessment



MATERIAL SAFETY DATA SHEET

In accordance with the EC REACH Regulation No. 1907/2006 and No. 453/2010 Classified and labelled in accordance with EC regulation No. 1272/2008 (CLP).

SECTION 16. OTHER INFORMATION

Users must have received instructions on performing the work and be familiar with the content of these safety requirements.

16.1 Attachments, deleted information, amendments

11.09.2013

 16.2 Key or legend to abbreviations and acronyms used in the safety data sheet

 REACH
 According to Regulation No. 1907/2006 of the European Union

 CLP
 REGULATION (EC) No 1272/2008

 DSD
 Classified and labelled according to Directive 67/548/EEC.

16.3 Literature references and sources of informationRegulation (EC) No. 1272/2008, manufacturer's safety data sheet: Cement based building products

16.4 Classification procedure Article 9(4), REGULATION (EC) No. 1272/2008

16.5 List of relevant R phrases, hazard statements, safety phrases and/or

precautionary statements
R37/38 Irritating to respiratory system and skin.

R41 H315 Risk of serious damage to eyes. Causes skin irritation.

H318 H335 Causes serious eye damage. May cause respiratory irritation.

16.6 Additional information:

Uninaks AS