



DECLARATION OF PERFORMANCE

No. 1504-UN001-01.02.2023

- 1. Product type unique identification code: MASONRY MORTAR NAKS M100
- Intended fields of use: MASONRY MORTAR NAKS M100 is a general-purpose masonry mortar (G) for laying internal and external load-bearing and non-load-bearing walls and posts. In the winter period, it is produced with antifreeze additives for use in temperatures up to -10° C
- 3. Manufacturer: AS Uninaks, Valuste tee 1, 90303 Lihula, Estonia
- 4. The system for assessment and verification of constancy of performance: System 2+
- 5. Harmonised standard: EVS-EN 998-2:2016

Notified body: Tallinna Sertifitseerimisasutus (Tallinn Certification Authority) (NB 1504)

6. Performance according to the declaration:

Essential characteristics	Performance	Harmonised technical specification
Compressive strength class*	M 10 (≥ 10 N/mm²)	
Mortar ingredients EN 1052-3 appendix C tabular value	≥ 0,15 N/mm ²	EVS-EN 998-2:2016
Adhesion strength	NPD	
Chloride content	< 0.1% CI	
Reaction to fire	A1	
Water absorption	≤ 0,5 kg/(m ² ·h ^{0,5})	
Water vapour permeability (tabular value)	15/35	
Thermal conductivity (tabular value)	0.93 W/mK	
Durability (GOST 5802)	F 15	
Dangerous substances	NPD	

^{*}No absorbent filter paper was used to prepare the test sample!

The above-described product performance corresponds to the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the above-mentioned manufacturer.

Signed by and in the name of the manufacturer:

Guido Piksar

Manager of Uninaks AS

01.02/2023