

DECLARATION OF PERFORMANCE

No. 1504-UN004-01.02.2023

1. Product type unique identification code: **PLOCK ADHESIVE PL50**
2. Intended fields of use: **PLOCK ADHESIVE PL50** is a general-purpose masonry mortar (G) for laying internal and external load-bearing and non-load-bearing walls and posts
3. Manufacturer: **AS Uninaks, Valuste tee 1, 90303 Lihula, Estonia**
4. The system for assessment and verification of constancy of performance: **System 2+**
5. Harmonised standard: **EVS-EN 998-2:2016**
Notified body: **Tallinna Sertifitseerimisasutus (Tallinn Certification Authority) (NB 1504)**
6. Performance according to the declaration:

Essential characteristics	Performance	Harmonised technical specification
Compressive strength class*	M 5 ($\geq 5 \text{ N/mm}^2$)	EVS-EN 998-2:2016
Mortar ingredients EN 1052-3 appendix C tabular value	$\geq 0,15 \text{ N/mm}^2$	
Adhesion strength	NPD	
Chloride content	$< 0.1\% \text{ Cl}$	
Reaction to fire	A1	
Water absorption	$\leq 1,0 \text{ kg}/(\text{m}^2 \cdot \text{h}^{0,5})$	
Water vapour permeability (tabular value)	15/35	
Thermal conductivity (tabular value)	0.9 W/mK	
Durability (GOST 5802)	F 15	
Dangerous substances	NPD	

*No absorbent filter paper was used to prepare the test sample!

The above-described product performance corresponds to the declared performance. This declaration of performance has been issued in accordance with Regulation (EU) No. 305/2011 under the sole responsibility of the above-mentioned manufacturer.

Signed by and in the name of the manufacturer:

Guido Piksar

Manager of Uninaks AS

01.02.2023

